NURIT 83020

Countertop Payment Solution



Top of the Countertop

The **NURIT 3020** is Lipman's top-of-the-line countertop: an advanced landline terminal that offers the flexibility required for versatile transaction processing in the rapidly-changing retail business market.

Merchants worldwide use this high-performance, compact POS terminal to quickly complete transactions with rapid online authorizations. The NURIT 3020 supports a wide range of applications, including traditional and EMV credit and debit, loyalty/gift cards, and check (using an external check reader) and proprietary card processing. Value-added applications such as prepaid phone card replacement are easily integrated. The NURIT 3020 accepts magnetic stripe cards, EMV and other ISO Smart Cards. It offers total security for merchants operating in permanent locations, such as department stores, supermarkets, shops and restaurants.

The durable and easy-to-use **NURIT 3020** incorporates

- a fast modem
- a fast, quiet & reliable thermal printer
- a rechargeable battery pack with fast charger
- Internet connectivity

It may also be fitted with

- an internal PIN pad
- a Smart Card reader
- up to 4 SAMs



The **NURIT 3020** is easily integrated with a variety of optional external devices such as

- PIN pads
- Barcode readers
- Check imagers
- Signature capture devices

Fast Downloading

The I4400 bps modem facilitates extremely fast downloading of software, parameters, diagnostic and other support information, thereby reducing cost of ownership.









Perfect for

Boutiques

Department Stores

 ${\sf Supermarkets}$

Discount Outlets

Cinema & Theater

Restaurants



SPECIFICATIONS

User interface

- 128 x 64 pixel graphical backlit display
- 20-key ergonometric keypad
- Menu-driven system
- Multi-language font support

Printer

- · Quiet thermal graphic printer
- 12 lines/second
- Automatic paper feeder
- 57 mm (2.25 in.) wide paper
- 8 dots/mm resolution

Magnetic stripe card reader

- · Vertical swipe, bi-directional
- Tracks I & 2 or 2 & 3

Communication

- 300 / 1200 / 2400 / up to 14,400 bps FastConnect landline modem
- · Synchronous or asynchronous
 - HDLC
 - TCP/IP

Processor and memory

- 32-bit Motorola EC68000 processor
- I to 2MB Flash memory for software
- 256KB to 2MB battery backed up RAM for user data, including RAM disk, with six month minimum data retention

Optional features

- EMV Level | Smart Card reader
- Up to four ISO 7816 contact SAMs
- Internal PINpad

Interfaces

- RS-232
- External PINpad
- Telephone and line

Software

- Powerful and proven NURIT Operating System (NOS)
- Easy to use SDK and debugging tools
- Download of application, parameters and/or NOS over phone or RS-232
 - EMV Level 2 Kernel Library available
 - \bullet Same applications run on all Lipman terminals

Approvals

- EMV Levels I and 2
- FCC parts 15 and 68
- TBR 21
- CE
- UL/TUV power supply

Dimensions

H 82 mm (3.23 in.) x W 108 mm (4.25 in.)
 x D 230 mm (9.06 in.)

Weight

• 780 g (1.72 lb)

Speaking the Language of Your Business

To **Do Business Better**, you need to communicate with your customers in their own language. To assure maximum flexibility and ease of use, The NURIT 3020's user interface is adapted to the local language in every market it serves, with customized applications for specific industry needs.



Managing Networks of Terminals

The NURIT Control Center makes it easy to support your NURIT 3020 terminal network. The sophisticated yet intuitive management system supports a variety of back-office functions for dynamic markets. It enables controlling remote terminals, and facilitates management of the wide range of market-specific applications that can run on NURIT 3020 terminals. Scalable and easily customizable, the Control Center offers various downloading capabilities, as well as simplified data collection and storage options that include inventory and financial record management.

Features

- Low cost, compact & comprehensive
- 20-button ergonomically designed keypad
- Fast, quiet & reliable built-in thermal printer
- Large back-lit graphical display
- Optional internal battery pack for up to five hours operating time
- Battery status monitor

- Built-in 14400 bps modem
- TCP/IP communications
- Optional built-in Smart Card reader
- Fast 32-bit processor
- Up to four SAM modules
- Multi-language font support
- Application software compatibility

Lipman, NURIT, NURIT 3020 and NURIT NOS are trademarks of Lipman Ltd., and may be registered in certain jurisdictions. Other company and brand, product and service names are trademarks or registered trademarks of their respective holder. Data and specifications are subject to change without notice.





LIPMAN International Headquarters

11 Ha'amal Street, Park Afek Rosh-Ha'ayin, ISRAEL 48092 Tel: +972 3 902 9730 Fax: +972 3 902 9731 e-mail: mail@lipman.co.il website: www.lipman.co.il

Lipman USA

50 Gordon Drive Syosset, NY USA 1179 I Tel: +1 516 484 9898 Fax: +1 516 484 9057 e-mail: info@lipmanusa.com website: www.lipmanusa.com

Lipman China

Room 601, Beijing Capital Times Square, No. 88 West Chang'an Avenue, Beijing P.R.C.100031 Tel: +86 10 839 13700/01/02 Fax: +86 10 839 13703 e-mail: lipman@public3.bta.net.cn website: www.lipman-china.com

Lipman Far East

7 Temasek Boulevard
The Penthouse #44-01
Suntec Tower I
Singapore 038987
Tel: +65 6430 6642
Fax: +65 6430 6644
e-mail: info@lipmanfareast.com
website: www.lipmanfareast.com

Lipman Spain

Calle Orense, n° 32 Ia planta, Ofc. 3 Madrid, SPAIN 28020 Tel: +34 91 598 2140 Fax: +34 91 597 0097 e-mail: nuritsys@lipman.es website: www.lipman.es

Lipman CIS

35 Myasnitskaya Street, Moscow, RUSSIA 101959 Tel: +7 095 933 2230 Fax: +7 095 204 1080 e-mail: lipman@gutatelecom.ru website: www.lipman.ru

Lipman Turkey

İstanbul AHL Serbest Bölgesi Şubesi Plaza No. 33 I 34830 Havalimanı-İstanbul Tel: +90 212 465 0424 Fax: +90 212 465 0423 e-mail: mail@lipman.com.tr website: www.lipman.com.tr