

# ATM

is 2000

The logo for TIDEL, featuring the word "TIDEL" in a blue, sans-serif font with a stylized orange and blue orbital path around the letters.

1 OZ	2 ABC	3 DEF	.
4 GHI	5 JKL	6 MNO	CLEAR
7 PRS	8 TUV	9 WXYZ	ENTER
*	0	#	

0000 0000 0000  
ATM Drive

is2000

The **Tidel is2000** represents the latest edition of our mid-range, feature-rich ATMs designed exclusively for off-premise use. The *is2000* sets a new standard of versatility, and its host of smart innovations reduce maintenance and expense.



Tidel Engineering, L.P.

2310 McDaniel Drive

Carrollton, TX 75006

Phone: 972.484.3358

1.800.678.7577

Fax: 972.484.1014

E-mail: sales@tidel.com

www.tidel.com

[s] standard features

[u] optional upgrades

**Specifications:**

Weight: 280 Lbs.

Power Requirements: 100-250v A/C 50/60Hz, 2.6 AMP.

Power Supply: 150 watt, individually fused with on/off switch.

**Power Connections:**

Unit recommended to be connected to a dedicated power circuit consisting of "Line", "Neutral" and "Ground" leads connected directly to the power distribution panel.

**Phone Line Requirements:**

Unit must be connected to a dedicated "tone" or "pulse" telephone that is terminated with a standard wall jack (RS-11C). To insure expected connectivity, unit should not share this line with any other equipment.

**Cabinet**

[s] UL291 Classified (short-door)

[u] UL291 'Listed' business hour (short door and long door)


[u] UL291 'Listed' level 1 (long door only)



**Modem**

[s] Standard modem

[u] 33.6 baud modem upgrade



**Dispenser**

[s] Fujitsu F-100 single cassette dispenser (2000-note capacity)

[u] Fujitsu F-400 dispenser upgrade (up to 4 cassettes)



**Other Options**

[u] Memory upgrade

[u] Electronic vault door locks

[u] Potted Encryption Board for greater tamper resistance

**Display**

[s] Monochrome display

[u] Color display



**Surge Suppressor**

