# **T77**

integrated high-performance POS terminal and printer









# Get high-performance transaction processing in compact terminal and printer:

- Improves productivity and reduces waiting time with fast printing
- Takes up less counterspace with small footprint
- Changes paper, ribbons and printer module easily and quickly
- Trains cashiers with easy-to-learn, simple-to-use 35-key keyboard
- Offers three printer options





# integrated high-performance POS terminal and printer

# Space-Saving High Performance

The Hypercom® T77 compact, high-performance terminal supports a wide range of applications including credit, debit and stored-value cards, as well as check and proprietary card processing. It is ideal for retail environments requiring very fast transaction times, for updating existing authoriziation-only equipment or for merchants moving to debit applications.

## Multiple Printer Options

The integrated, high-speed printer on the T77 is available in thermal, sprocket or friction types. All modules are easily replaceable and eliminate reliability problems. The sprocket printer option allows the T77 to print transaction-specific information inside preprinted, multi-part retail vouchers for high-quality, professional cardholder receipts.

## Additional Benefits

Specific price/performance benefits of the T77 include savings on user training, reduced telephone line costs, shorter processing and shorter settlement times. It features a broad range of telecommunications, display, keypad, card reader and system connectivity options that enable it to meet the demands of a sophisticated, everchanging marketplace.

#### World Headquarters/ North America

Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053

Tel: +1.602.504.5000 Fax: +1.602.866.5380

#### Latin America

Hypercom Industria e Comercio LTDA Centro Empresarial Atibaia Rodovia Dom Pedro I, KM 87, 5 Av. Tegula, 888-Ponte Alta Atibaia 12940-000, Brazil Tel: +55.11.4417.7000 Fax: +55.11.4417.7060 Asia/Pacific Rim

Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay, Kowloon Hong Kong Tel: +85.2.2561.6800

Europe/Middle East/Africa

Hypercom EMEA, Inc.

Únit 2, Woking Eight

Woking, GU21 5SB,

United Kingdom Tel: +44.1483.718600

Fax: +44.1483.718601

Forsyth Road

©2002-2004 Hypercom Corporation, all rights reserved. Hypercom and the Hypercom logo are registered trademarks of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Celebrating 26 years of technology excellence, innovation and leadership, Hypercom Corporation is a leading global provider of electronic payment solution that add value at the point-of-transaction for consumers merchants and acquirers, and yield increased profitability for its customers.

Widely recognized as the global payment technology innovator, Hypercom delivers comprehensive card payment terminal, network and server solutions that help merchants and financial institutions generate revenues and increase grafts.

# Specifications:

### Display

LCD: 2 lines x 20 characters Backlight: 25,000 hours (half-life calculated)

Silicone rubber: 35 kevs

Reliability: 450,000 operations (calculated)

## Card Reader

Magnetic Stripe: Tracks 1, 2 (standard); Track 3 and JIS II (optional) Reliability: 900,000 reads (calculated)

#### Communications

Modem: 2400 or 1200 bps; synchronous (SDLC) & asynchronous (Visa I & II); 9600 bps (optional) LAN: RS-485 Hypercom LAN

PIN Pad Port: 2-wire or 4-wire, RS-422 Peripheral: S7C, S7SC, S8, P7E, ICE, HFT 105

T77-T

Type: Thermal, 48 columns Paper width: 3.15 in/80 mm Paper type: Multi-ply Reliability: 5 million lines (calculated)

Type: Friction, 40 columns Paper width: 3.0 in/76.19 mm Paper type: 1, 2, 3-ply Reliability: 2 million lines (calculated)

Type: Sprocket, 23 columns **Paper width:** 3.0 in/76.19 mm Paper type: 1, 2, 3-ply

Reliability: 2 million lines (calculated)

## Memory

RAM: Up to 1 MB EPROM: 32KB

RAM backup: 5-year battery

#### Power

AC: 100-240 V AC, 50/60 Hz DC: 24 V, 1 A

## Footprint

9.25 in x 6.75 in x 4.25 in/23.49 cm x 17.15 cm x 10.79 cm

## Weiaht

Approximate: 3.65 lbx/1.36 kg

## Environment

Temperature: 0-45°C/32- 110°F Humidity: Max 85%, non-condensing ESD: 12,000 volts

Reliability 100,000 hours (MTBF calculated), excluding printer

Specifications subject to change without notice.

940078-001. Rev. C

