

ATM

00851800



TIDEL

1 OZ	2 ABC	3 DEF	.
4 GHI	5 JKL	6 MNO	CLEAR
7 PRS	8 TUV	9 WXY	ENTER
*	0	#	

0000 0000 0000
Date Due

The **Tidel is800** represents the newest edition of our low-end focus function ATMs designed exclusively for off-premise use. The *is800* sets a new standard of affordability without compromising quality and performance.



Tidel Engineering, L.P.

2310 McDaniel Drive

Carrollton, TX 75006

Phone: 972.484.3358

1.800.678.7577

Fax: 972.484.1014

E-mail: sales@tidel.com

www.tidel.com

Specifications:

Weight: 280 Lbs.

Power Requirements: 100-250v A/C 50/60Hz, 2.6 AMP.

Power Supply: 50 watt with easy access A/C plug.

Power Connections:

Unit recommended to be connected to a dedicated power circuit consisting of "Line", "Neutral" and "Ground" leads connected directly to the power distribution panel.

Phone Line Requirements:

Unit must be connected to a dedicated "tone" or "pulse" telephone that is terminated with a standard wall jack (RS-11C). To insure expected connectivity, unit should not share this line with any other equipment.


[s] standard features

[u] optional upgrades

Modem

[s] Standard modem

[u] 33.6 baud modem upgrade



Cabinet

[s] UL291 Classified (short-door)



Dispenser

[s] LG Mini CDM single cassette dispenser (800-note capacity)



Other Options

[u] Surge suppressor

[u] Potted Encryption Board for greater tamper resistance

Display

[s] Monochrome display

[u] Color display

